

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: SOUDAL PRIMER 100

Other Means of Identification: Mixture

Product Code: 44711

Recommended Use of the Chemical and Restriction on Use: Primer

Details of Manufacturer or Importer:

Soudal Australia Pty Ltd
Unit 1, 29 Prince William Drive
Seven Hills NSW 2147

Phone Number: 02 8678 7449

Emergency telephone number: 1300 507 011

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Signal Word Warning

Hazard Statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 1)

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P273	Avoid release to the environment.
P243	Take precautionary measures against static discharge.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P370+P378	In case of fire: Use for extinction: CO ₂ , powder or water spray.
P391	Collect spillage.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

108-67-8	mesitylene ⚠ Flam. Liq. 3, H226; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335	2.5-<25%
100-41-4	Benzene, ethyl- ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. (Inhalation) 4, H332	10-<25%
140921-24-0	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate ⚠ Skin Sens. 1, H317	10-<25%
95-63-6	Benzene, 1,2,4-trimethyl- ⚠ Flam. Liq. 3, H226; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. (Inhalation) 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<25%
64742-95-6	Solvent naphtha (petroleum), light arom. ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; Flam. Liq. 4, H227; Aquatic Acute 2, H401	10-<25%
1330-20-7	Benzene, dimethyl- ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. (Dermal) 4, H312; Acute Tox. (Inhalation) 4, H332; Skin Irrit. 2, H315	10-<25%

(Contd. on page 3)

SAFETY DATA SHEET














According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 2)

540-84-1	2,2,4-trimethylpentane  Flam. Liq. 2, H225;  Asp. Tox. 1, H304;  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Irrit. 2, H315; STOT SE 3, H336	1-≤2.5%
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  Acute Tox. (Inhalation) 3, H331;  Resp. Sens. 1, H334;  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.3-≤0.5%
53880-05-0	Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer  Skin Sens. 1, H317; STOT SE 3, H335	>20%
98-82-8	cumene  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H335	1-≤10%

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

Ingestion:

If swallowed, do not induce vomiting. Give a glass of water. Never give anything by mouth to an unconscious person. Seek medical attention.

5 . FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Polyvalent foam, BC powder and carbon dioxide.

Specific Hazards Arising from the Chemical:

Containers close to fire should be removed if safe to do so. Use water to keep fire exposed containers cool. Vapors are heavier than air and may travel long distance to a source of ignition and flash back. Hazardous combustion products include oxides of carbon and nitrous vapours.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 . ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

(Contd. on page 4)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 3)

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools. Clean contaminated surfaces with an excess of water.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Protect from direct sunlight, heat, sparks, open flames and other sources of ignition. Keep away from strong oxidising agents and acids. Maximum storage time is one year.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:

100-41-4 Benzene, ethyl-

NES	STEL: 543 mg/m ³ , 125 ppm TWA: 434 mg/m ³ , 100 ppm
-----	---

1330-20-7 Benzene, dimethyl-

NES	STEL: 655 mg/m ³ , 150 ppm TWA: 350 mg/m ³ , 80 ppm
-----	--

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

NES	STEL: 0.07 mg/m ³ TWA: 0.02 mg/m ³ Sen, as -NCO
-----	---

98-82-8 cumene

NES	STEL: 375 mg/m ³ , 75 ppm TWA: 125 mg/m ³ , 25 ppm Sk
-----	---

108-67-8 mesitylene

TWA	100 mg/m ³ , 20 ppm (EU)
-----	-------------------------------------

95-63-6 Benzene, 1,2,4-trimethyl-

TWA	100 mg/m ³ , 20 ppm (EU)
-----	-------------------------------------

Engineering Controls:

Maintain air concentration below occupational exposure standards, providing adequate ventilation. Use explosion-proof ventilating equipment.

Respiratory Protection:

Use a Safe Work Australia approved full face supplied air respirator if high airborne concentrations of the material are present. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Protective gloves (teflon, viton, nitrile rubber) and protective clothing. See Australian Standards AS/NZS 2161, 2210.1 and 2210.2 for more information.

(Contd. on page 5)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 4)

Eye and Face Protection:

Safety glasses with top and side shields or goggles. See Australian/New Zealand Standards AS/NZS 1336 and 1337 for more information.

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form:	Liquid
Colour:	Variable in colour, depending on the composition.
Odour:	Solvent like odour
Odour Threshold:	Not determined.
pH-Value:	Not determined.
Melting point/Melting range:	Not determined.
Initial Boiling Point/Boiling Range:	Not determined.
Flash Point:	47 °C
Flammability:	Flammable
Auto-ignition Temperature:	Not determined.
Decomposition Temperature:	Not determined.
Explosion Limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour Pressure:	Not determined.
Density:	Not determined.
Relative Density at 20 °C:	1 g/cm ³
Vapour Density at 20 °C:	>1 g/cm ³
Evaporation Rate:	Not determined.
Viscosity at 40 °C:	>20.5 mm ² /s (kinematic)
VOC:	78 %

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames and other sources of ignition.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: Oxides of carbon and nitrous vapours.

11 . TOXICOLOGICAL INFORMATION

Toxicity:

LD₅₀/LC₅₀ Values Relevant for Classification:

100-41-4 Benzene, ethyl-

Oral	LD ₅₀	3500 mg/kg (rat)
Dermal	LD ₅₀	17800 mg/kg (rabbit)

95-63-6 Benzene, 1,2,4-trimethyl-

Oral	LD ₅₀	5000 mg/kg (rat)
------	------------------	------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD ₅₀	>6800 mg/kg (rat)
Dermal	LD ₅₀	>3400 mg/kg (rab)

(Contd. on page 6)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 5)

Inhalation	LC ₅₀ /4 h	>10.2 mg/l (rat)
1330-20-7 Benzene, dimethyl-		
Oral	LD ₅₀	4300 mg/kg (rat)
Dermal	LD ₅₀	2000 mg/kg (rabbit)
53880-05-0 Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer		
Oral	LD ₅₀	> 5000 mg/kg (rat)
Inhalation	LC ₅₀	> 5.01 mg/L (rat)
4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate		
Oral	LD ₅₀	> 2500 mg/kg (rat)
108-67-8 mesitylene		
Inhalation	LC ₅₀	24 mg/L / 4 hour (rat)
98-82-8 cumene		
Oral	LD ₅₀	1400 mg/kg (rat)
Dermal	LD ₅₀	12300 mg/kg (rabbit)
Inhalation	LC ₅₀ /4 h	24.7 mg/l (mouse)
540-84-1 2,2,4-trimethylpentane		
Oral	LD ₅₀	3310 mg/kg (rat)
Dermal	LD ₅₀	>2000 mg/kg (rabbit)
Inhalation	LC ₅₀	> 14.5 mg/L / 4 hour (rat)

Acute Health Effects

Inhalation:

May cause irritation of the nasal mucous membranes and the respiratory tract. Exposure to high concentrations may cause narcosis.

Skin: May cause slight skin irritation.

Eye: May cause slight eye irritation.

Ingestion: Ingestion is not considered a potential route of exposure.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met.

Respiratory or Skin Sensitisation: Sensitisation possible through skin contact.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity:

Xylenes is classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Ethylbenzene and cumene are classified by IARC as Group 2B - Possibly carcinogenic to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

May cause respiratory irritation.

May cause drowsiness and dizziness.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

Chronic Health Effects: Repeated or prolonged contact may cause skin rash and inflammation.

(Contd. on page 7)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 6)

Existing Conditions Aggravated by Exposure: No information available

12 . ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic toxicity:

Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

53880-05-0 Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer	
EC50 / 48 h	83.7 mg/L (daphnia)
108-67-8 mesitylene	
LC50 / 96 h	13 mg/L (fish)
95-63-6 Benzene, 1,2,4-trimethyl-	
EC50 / 48 h	3.6 mg/L (daphnia)
LC50 / 96 h	7.72 mg/L (flathead minnows)
98-82-8 cumene	
LC50 / 96 h	2.7 mg/L (fish)
1330-20-7 Benzene, dimethyl-	
EC50 / 48 h	7.4 mg/L (daphnia)
LC50 / 96 h	3.77 mg/L (fish)
100-41-4 Benzene, ethyl-	
EC50 / 48 h	75 mg/L (daphnia)
LC50 / 96 h	4.2 mg/L (fish)

Persistence and Degradability: No information available

Bioaccumulative Potential: No information available

Mobility in Soil: No information available

13 . DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 . TRANSPORT INFORMATION

UN Number	1263
Proper Shipping Name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Dangerous Goods Class	3
Packing Group: ADG, IMDG, IATA	III
Marine pollutant:	Yes Symbol (fish and tree)
Hazchem Code:	.3Y

(Contd. on page 8)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 17.12.2015

Revision: 17.12.2015

Product Name: SOUDAL PRIMER 100

(Contd. of page 7)

Special Provisions: 163, 223
Limited Quantities: 5L
Packagings & IBCs - Packing Instruction: P001, IBC03, LP01
Packagings & IBCs - Special Packing Provisions: PP1
Portable Tanks & Bulk Containers - Instructions: T2
Portable Tanks & Bulk Containers - Special Provisions: TP1, TP29

15 . REGULATORY INFORMATION**Australian Inventory of Chemical Substances:**

53880-05-0	Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer
108-67-8	mesitylene
100-41-4	Benzene, ethyl-
95-63-6	Benzene, 1,2,4-trimethyl-
64742-95-6	Solvent naphtha (petroleum), light arom.
540-84-1	2,2,4-trimethylpentane
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:
 Poisons Schedule: 5

16 . OTHER INFORMATION**Date of Preparation or Last Revision:** 17.12.2015**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au**Abbreviations and acronyms:**

ADG: Australian Dangerous Goods
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds
 LC₅₀: Lethal concentration, 50 percent
 LD₅₀: Lethal dose, 50 percent
 IARC: International Agency for Research on Cancer
 STEL: Short Term Exposure Limit
 TWA: Time Weighted Average
 NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Data compared to the previous version altered: Section 1.**Disclaimer**

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Soudal Australia Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.